

Product Specifications - EnviroLeather®

Collection Name	Berkshire 2.0	
Content	50% Polycarbonate-based polyurethane (face) 50% Polyester Circular Knit (back)	
Width	54 inches minimum	
Abrasion	Wyzenbeek	Exceeds 500,000 double rubs
Colorfastness to Light	AATCC TM 16.3, Option 3	Grade 5 minimum @ 200 hours
Hydrolysis Resistance	ISO 1419 C	Exceeds 15 weeks
Flammability	NFPA 260-A	CLASS 1
	CA TB 117-2013 Section 1	PASS
	UFAC	CLASS 1
	ASTM E84	CLASS 2
CFFA HC 201B Standards	PASS	

*Abrasion test results exceeding ACT Voluntary Performance Guidelines minimums are not an indicator of product lifespan.

ACT Registered Certification Marks



Health Benefits

GreenScreen Certified®
 Flame-retardant free: California AB-2998 compliant
 PFAS-free: California AB-2771 compliant
 Low VOC emissions: California 01350 compliant
 PVC - Free

Performance Characteristics

Chemical resistant: passes CFFA-101
 Stain resistant: passes CFFA-142
 Liquid barrier
 Resists wrinkling & puddling

Care & Maintenance

Cleaning Code W/S
 Bleach cleanable (see website for additional cleaners)