

## Product Specifications - EnviroSil®

<b>Collection Name</b>	Niagara	
<b>Content</b>	50% Silicone (face) 50% Polyester knit (back)	
<b>Width</b>	54 inches minimum	
<b>Abrasion</b>	Wyzenbeek	Exceeds 500,000 double rubs
<b>Colorfastness to Light</b>	AATCC TM 16.3, Option 3	Grade 4.5 minimum @ 200 hours
<b>UV Stability</b>	ASTM D4329-05 (QQUV)	Exceeds 1500 hours
<b>Hydrolysis Resistance</b>	ASTM D3690-02	Exceeds 15 weeks
<b>Flammability</b>	NFPA 260	CLASS 1
	CA TB 117-2013 Section 1	PASS
	UFAC	CLASS 1
	IMO Part 8	PASS
	ASTM E84	CLASS 2

\*Abrasion test results exceeding ACT Voluntary Performance Guidelines minimums are not an indicator of product lifespan.

### ACT Registered Certification Marks



#### Health Benefits

GreenScreen Certified®  
 Flame-retardant free: California AB-2998 compliant  
 PFAS-free: California AB-2771 compliant  
 Low VOC emissions: California 01350 compliant  
 PVC - Free

#### Performance Characteristics

Chemical resistant: passes CFFA-101  
 Stain resistant: passes CFFA-142  
 Liquid barrier  
 Resists wrinkling & puddling

#### Care & Maintenance

Cleaning Code W/S  
 Bleach cleanable (see website for additional cleaners)