


**Product Specifications - EnviroWoven®**

powered by  **SUPREEN®**

<b>Collection Name</b>	Tweed	
<b>Content</b>	88% Polyester 10% Polyurethane 2% Silicone	
<b>Width</b>	54 inches minimum	
<b>Abrasion</b>	Wyzenbeek	Exceeds 100,000 double rubs
<b>Seam Slippage</b>	ASTM D4034-92	Warp: 87.5 lbs Fill: 93.0 lbs
<b>Pilling</b>	ASTM D3511	CLASS 5
<b>Colorfastness to Light</b>	AATCC TM 16.3, Option 3	Grade 5 minimum @ 40 hours
<b>Flammability</b>	NFPA 260	CLASS 1
	CA TB 117-2013 Section 1	PASS
	UFAC	CLASS 1

\*Abrasion test results exceeding ACT Voluntary Performance Guidelines minimums are not an indicator of product lifespan.

**ACT Registered Certification Marks**



**Health Benefits**

GreenScreen Certified®  
 Flame-retardant free: California AB-2998 compliant  
 PFAS-free: California AB-2771 compliant  
 Low VOC emissions: California 01350 compliant  
 PVC - Free

**Performance Characteristics**

Stain resistant  
 Liquid barrier  
 Supple hand

**Care & Maintenance**

Cleaning Code W/S  
 Bleach cleanable (appropriate for non-clinical healthcare settings)